

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : G11B 20/00, 23/28, G06K 19/07		A1	(11) International Publication Number: WO 00/23994 (43) International Publication Date: 27 April 2000 (27.04.00)
(21) International Application Number: PCT/US99/23630 (22) International Filing Date: 13 October 1999 (13.10.99) (30) Priority Data: 60/104,667 16 October 1998 (16.10.98) US 09/199,620 25 November 1998 (25.11.98) US (71) Applicant: INTERMEC IP CORP. [US/US]; 21900 Burbank Boulevard, Woodland Hills, CA 91367-7418 (US). (72) Inventors: BRADY, Michael, John; 72 Seven Oaks Lane, Brewster, NY 10509 (US). DUAN, Dah-Wei; 1185 Park Lane, Yorktown Heights, NY 10598 (US). JOHNSON, Glen, Walden; 2819 Birch Street, Yorktown Heights, NY 10598 (US). MOSKOWITZ, Paul, Andrew; 2015 Hunterbrook Road, Yorktown Heights, NY 10598 (US). TETZLAFF, Linda; 37 Fox Den Road, Mount Kisco, NY 10549 (US). (74) Agents: BERLINER, Brian, M.; O'Melveny & Myers LLP, 400 South Hope Street, Los Angeles, CA 90071-2899 (US) et al.			(81) Designated States: JP, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>

(54) Title: **SMART OPTICAL STORAGE MEDIA**

(57) Abstract

An optical storage medium is disclosed. The optical storage medium comprises an optical disc (100) which includes integral information storage (112) and communication apparatus (130) for storing and communicating information to an external system. The information storage and communication apparatus comprises a circuit (132) including memory for storing information and a communication device (134) for communicating the information with the external system.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

SMART OPTICAL STORAGE MEDIACross-Reference to Related Applications

The present application claims the benefit under 35 U.S.C. § 119(e) of U.S. Provisional Application No. 60/104,667, filed October 16, 1998. Said U.S. Provisional Application No. 60/104,667 is herein incorporated by reference in its entirety.

Incorporation by Reference

The following US Patents and Patent Applications are hereby incorporated herein by reference in their entirety:

U.S. Patents

	<u>Patent N°</u>	<u>Issue Date</u>	<u>Filing Date</u>	<u>Attorney Docket N°</u>
10	5,521,601	05/28/96	04/21/95	YO995-0088
	5,528,222	06/18/96	09/09/94	YO994-180
	5,538,803	07/23/96	11/23/94	YO994-0073
	5,550,547	08/27/96	09/12/94	YO994-185
15	5,552,778	09/03/96	11/23/94	YO994-0232
	5,554,974	09/10/96	11/23/94	YO994-0071
	5,563,583	10/08/96	11/23/94	YO994-070
	5,565,847	10/15/96	11/23/94	YO994-0072
	5,606,323	02/25/97	08/31/95	YO995-157
20	5,635,693	06/03/97	02/02/95	YO994-0215
	5,673,037	09/30/97	09/09/94	YO994-184
	5,680,106	10/21/97	10/27/95	YO995-0219
	5,682,143	10/28/97	09/09/94	YO994-170
	5,729,201	03/17/98	06/29/95	YO995-109
25	5,729,697	03/17/98	04/24/95	YO995-076
	5,736,929	04/07/98	06/07/96	YO996-085

	<u>Patent N°</u>	<u>Issue Date</u>	<u>Filing Date</u>	<u>Attorney Docket N°</u>
	5,739,754	04/14/98	07/29/96	YO996-115
	5,767,789	06/16/98	08/31/95	YO994-213
	5,777,561	07/07/98	09/30/96	YO996-178
5	5,786,626	07/28/98	03/25/96	YO996-031
	5,812,065	09/22/98	12/08/95	YO995-124X
	5,821,859	10/13/98	06/07/96	YO996-084

U.S. Nonprovisional Patent Applications

	<u>Application N°</u>	<u>Filing Date</u>	<u>Attorney Docket N°</u>
10	08/681,741	07/29/96	YO996-037
	08/626,820	04/03/96	YO995-158
	08/646,539	05/08/96	YO996-068
	08/681,741	07/29/96	YO996-037
	08/694,606	08/09/96	YO995-218
15	08/790,639	01/29/97	YO997-024
	08/790,640	01/29/97	YO997-023
	08/733,684	10/17/96	YO996-195
	08/862,149	05/23/97	YO997-116
	08/862,912	05/23/97	YO997-115
20	08/862,913	05/23/97	YO997-114
	08/909,719	08/12/97	YO995-109B
			(allowed)
	08/935,989	10/23/97	YO997-310
	EH 372 217 464 US	07/10/98	YO896-0212R1
25	09/122,300	07/24/98	YO897-259R

U.S. Provisional Patent Applications

	<u>Application N°</u>	<u>Filing Date</u>	<u>Attorney Docket N°</u>
	60/068,373	12/22/97	YO894-0206P1
	60/073,102	01/30/98	YO897-0028P1
5	60/074,605	02/13/98	YO897-0259P1
	60/077,879	03/13/98	YO997-0038P1
	60/078,100	03/16/98	YO897-0657P1
	60/078,226	03/16/98	YO897-0658P1
	60/078,287	03/17/98	YO897-0661P1
10	60/091,350	07/01/98	YO897-0259P2
	60/078,304	03/17/98	YO897-0662P1
	60/090,637	06/25/98	YO896-0212P2
	60/091,352	07/01/98	YO897-0673P1
	60/091,350	07/01/98	YO897-0259P2
15	60/093,088	07/16/98	38384P1
	60/099,298	09/04/98	YO894-0206P3
	EI 837 644 898 US	09/17/98	38402P1

The following further documents are also incorporated herein by reference in their entirety:

20 IBM Technical Disclosure Bulletin

IBM Technical Disclosure Bulletin: Vol. 38 N° 08, August 1995, page 17, "Multifunction Credit Card Package," by Brady, Moskowitz, and Murphy (published pseudonymously).

Literature Reference

25 D. Friedman, H. Heinrich, D. Duan, "A low-power CMOS integrated circuit for field-powered radio frequency identification (RFID) tags," 1997 Digest of Technical Papers of the IEEE International Solid-State Circuits Conference (ISSCC), San Francisco, CA, February 1997.

PCT Published International Applications

	<u>Application N°</u>	<u>Filing Date</u>	<u>Attorney Docket</u> <u>N°</u>
	PCT/GB96/00061	01/15/96	UK 9-94-066 PCT
5	PCT/EP95/03703	10/20/95	YO994-242 PCT

UK Published Application

	<u>Application N°</u>	<u>Filing Date</u>	<u>Attorney Docket</u> <u>N°</u>
	9710025.9	05/19/97	YO9-96-084

Field of the Invention

The present invention relates generally to optical storage media (i.e., optical discs including compact disc (CD), compact disc read only memory (CD-ROM), digital versatile (video) disc (DVD), laserdisc, etc.), and more specifically to smart optical storage media having information storage and communication apparatus and methods for their use.

Background of the Invention

Optical storage media such as optical discs provide high density, digital storage of information and data in computer, video, and audio applications. Often, optical discs contain information (i.e., movies, music, computer programs, games, etc.) which may be proprietary or which may be subject to copyright protection. For this reason, such optical discs are subject to theft or unauthorized copying (e.g., counterfeiting). Further, optical discs are capable of holding an extremely large amount of information. Thus, optical discs often contain information which may be viewed (or heard) by a wide audience as well as information which is meant for more limited groups. For example, optical discs may contain information (i.e., movies, songs, games, etc.) capable of being viewed by audiences of all ages as well as information which should only be viewed by adults. Similarly, an optical disc may contain information of a sensitive or proprietary nature which is to be viewed only by certain persons within an organization.

Consequently, it would be advantageous to provide a smart optical disc which includes a means of authentication that is secure against theft or counterfeit. The smart optical disc could include index information which could be used to enable or disable the use of sections of the disc and could be capable of storing data such as a record of usage of the disc's contents.

Summary of the Invention

Accordingly, the present invention is directed to a novel optical storage media comprising an optical disc which includes integral information storage and communication apparatus for storing and communicating information to an external system. The information storage and communication apparatus
5 comprises a circuit including memory for storing information and a communication device for communicating the information with the external system.

In an exemplary embodiment, the circuit comprises a radio frequency identification (RFID) transponder laminated between the outer protective layers
10 of the optical disc. The RFID transponder includes a radio frequency identification integrated circuit (RFID IC) having memory for storing information coupled to an antenna. The RFID transponder may be utilized by external systems to provide functions such as authentication of the disc, indexing of
15 information recorded to the disc, enablement/disablement of the disc, recording of the number of times the disc has been played, and the like.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the invention claimed. The accompanying drawings, which are
20 incorporated in and constitute a part of the specification, illustrate an embodiment of the invention and together with the general description, serve to explain the principles of the invention.

Brief Description of the Drawings

The numerous objects and advantages of the present invention may be
25 better understood by those skilled in the art by reference to the accompanying figures in which:

FIG. 1 is a top plan view of an optical disc having an prefabricated RFID transponder;

FIG. 2 is a cross-sectional view of the optical disc shown in FIG. 1;

FIG. 3 is a top plan view of an optical disc having a prefabricated RFID transponder wherein the data storage layer is utilized as a conducting ground plane;

FIG. 4 is a cross-sectional view of the optical disc shown in FIG. 3;

5 FIG. 5 is a top plan view of an optical disc having a radio frequency identification integrated circuit (RFID IC) chip and antenna integrated within its annular non-storage area wherein the antenna is a dipole antenna;

FIG. 6 is a top plan view of the annular non-storage area of an optical disc having a radio frequency identification integrated circuit (RFID IC) chip and
10 antenna integrated within the area wherein the antenna is a conforming loaded dipole antenna;

FIG. 7 is a cross-sectional view of the optical discs shown in FIGS. 5 and 6;

FIG. 8 is a top plan view of an optical disc having a radio frequency
15 identification integrated circuit (RFID IC) chip and antenna integrated within its annular non-storage area wherein the antenna is a meander dipole antenna;

FIG. 9 is a top plan view of the annular non-storage area of an optical disc having a radio frequency identification integrated circuit (RFID IC) chip and
20 antenna integrated within the area wherein the antenna is a conforming meander antenna;

FIG. 10 is a top plan view of an optical disc having a radio frequency identification integrated circuit (RFID IC) chip and antenna integrated within the area wherein the antenna is a loop antenna;

FIG. 11 is a top plan view of the annular non-storage area of an optical
25 disc illustrating an alternative loop antenna geometry;

FIG. 12 is a top plan view of the annular non-storage area of an optical disc illustrating an alternative loop antenna geometry;

FIG. 13 is a top plan view of an optical disc having a radio frequency identification integrated circuit (RFID IC) chip and antenna integrated within its annular non-storage area wherein the antenna is a spiral antenna;

FIG. 14 is a top plan view of the annular non-storage area of an optical disc having a radio frequency identification integrated circuit (RFID IC) chip and antenna integrated within the area wherein the antenna is a circular slot antenna;

FIG. 15 is a top plan view of the annular non-storage area of an optical disc having a radio frequency identification integrated circuit (RFID IC) chip and antenna integrated within the area wherein the antenna is a curvilinear slot antenna;

FIG. 16 is a top plan view of the annular non-storage area of an optical disc having a radio frequency identification integrated circuit (RFID IC) chip and antenna integrated within the area wherein the antenna is a split monopole antenna;

FIG. 17 is a top plan view of the annular non-storage area of an optical disc having a radio frequency identification integrated circuit (RFID IC) chip and antenna integrated within the disc wherein the antenna is a split monopole antenna;

FIG. 18 is a top plan view of an optical disc having a radio frequency identification integrated circuit (RFID IC) chip and antenna integrated within the disc wherein the antenna is a linearly polarized patch antenna;

FIG. 19 is a top plan view of an optical disc having a radio frequency identification integrated circuit (RFID IC) chip and antenna integrated within the disc wherein the antenna is a circularly polarized patch antenna;

FIG. 20 is a top plan view of an optical disc having a radio frequency identification integrated circuit (RFID IC) chip and antenna integrated within the disc wherein the antenna is a conforming patch antenna;

FIG. 21 is a top plan view of the annular non-storage area of an optical disc having a radio frequency identification integrated circuit (RFID IC) chip and

antenna integrated within the area wherein the antenna is an annular patch antenna;

FIG. 22 is a cross-sectional view of the optical discs shown in FIGS. 18, 19, 20 and 21;

5 FIG. 23 is a top plan view of an optical disc having a radio frequency identification integrated circuit (RFID IC) chip and antenna integrated within the disc wherein the data storage layer is utilized as part of the antenna;

FIG. 24 is a cross-sectional view of the optical disc shown in FIG. 23;

10 FIG. 25 is a top plan view of an optical disc having a radio frequency identification integrated circuit (RFID IC) chip and antenna integrated within the disc wherein the data storage layer is utilized as part of the antenna;

FIG. 26 is a top plan view of an optical disc having a radio frequency identification integrated circuit (RFID IC) and conforming patch antenna integrated within the disc wherein the data storage layer is utilized as the
15 ground plane for the antenna;

FIG. 27 is a cross-sectional view of the optical disc shown in FIG. 26;

FIG. 28 is a top plan view of an optical disc having a radio frequency identification integrated circuit (RFID IC) and patch antenna integrated within the disc wherein the data storage layer is utilized as the ground plane for the
20 antenna;

FIG. 29 is a top plan view of an optical disc having circuit including memory interconnected with a surface contact connector disposed on the surface of the optical disc;

FIG. 30 is a block diagram illustrating a system for playing and/or
25 recording optical discs in accordance with the present invention;

FIG. 31 is a perspective view illustrating a system for interrogating optical discs of the present invention in a point of sale environment;

FIG. 32 is a perspective view further illustrating the hand-held interrogator and an optical disc as shown in FIG. 21;

FIG. 33 is a perspective view illustrating a system for interrogating optical discs of the present invention wherein the optical discs are crated for shipping; and

FIG. 34 is a top plan view of an alternative system for interrogating optical discs wherein the discs are crated for shipping.

Detailed Description of the Invention

The present invention provides an optical disc having an integral information storage and communication apparatus for storing and communicating information to an external system. The information storage and communication apparatus comprises a circuit including memory for storing information and a communication device for communicating the information between the circuit and the external system. The circuit is laminated between the outer protective layers of the optical disc so that it is protected from damage and can not be removed from the disc without physically altering or damaging the disc itself.

Referring now to FIGS. 1 through 29, optical discs in accordance with exemplary embodiments of the present invention are shown. The optical discs 100 may comply with any of numerous established formats, formats which are presently proposed or in development, or formats which may be proposed and developed in the future. Such formats include, but are not limited, to audio Compact Disc (CD), Compact Disc-Read Only Memory (CD-ROM), Readable/Writeable Compact Disc (i.e., CD-R, CD-RW formats), Digital Versatile (Video) Disc (i.e., DVD, DVD-ROM, DVD-R, DVD-RW, DVD-RAM formats), PhotoCD, Laserdisc, etc.

Such optical discs 100 typically include one or more data storage layers 112 (one is shown) sandwiched between distal outer protective layers 114 & 116. Each data storage layer 112 comprises an annulus 118 formed of metal (typically aluminum) or a metallized material having at least one polished surface 120 capable of reflecting laser light emitted from an optical disc playing

apparatus [hereinafter optical disc drive]. Information may be physically inscribed onto the surface 120 in the form of a spiral shaped track of pits and lands. In this manner, the information may be digitally recorded to the optical disc 100. The data storage layer 112 is laminated between the first and second
5 outer layers 114 & 116. The outer layers 114 & 116 may be made of a transparent plastic to allow laser light from the optical disc drive to penetrate to the reflective surface (or surfaces) of the data storage layer 112. A circular aperture 122 may extend through the disc 100 at its center. The aperture 122 allows a drive mechanism (not shown) within the optical disc drive to engage
10 and spin the disc 100. Typically, the perimeter 124 of the aperture 122 and the inner edge 126 of the annulus 122 define an annular non-storage area 128 which does not contain optically encoded data (the data storage layer 122 does not extend into the area 128).

As shown in FIGS. 1 through 28, the information storage and
15 communication circuit may comprise a radio frequency identification (RFID) transponder 130 laminated between the outer layers 114 & 116 of the optical disc 100. The RFID transponder 130 may communicate with an external system (i.e., an optical disc player, an optical disc recorder, an RFID system, etc.) to provide functions such as authentication of the optical disc 100,
20 indexing of information recorded to the optical disc 100, enablement/disablement of playback the optical disc 100 by a disc drive, tracking of the number of times the disc 100 has been played, and the like.

The RFID transponder 130 comprises a low power radio frequency identification integrated circuit (RFID IC) 132 including a signal processing
25 section and an RF processing section (typically referred to as a front end) interconnected to an antenna 134. The front end includes interface circuitry which provides the facility to direct and accommodate the interrogation field energy for powering purposes in passive transponders and triggering of the transponder response. The front end can be any known front end design
30 used with an antenna. Examples of front ends are well known. See, for

example, the Hewlett Packard "Communications Components GaAs & Silicon Products Designer's Catalog" (i.e., page 2-15) which is herein incorporated by reference in its entirety. A typical front end is also described in U.S. Patent Application Serial No. 08/790,639 to Duan, et al. filed January 29, 1997 which
5 is herein incorporated by reference in its entirety. The signal processing section may comprise control and processing circuitry and memory. Typical memory may include, for example, read-only memory (ROM), random access memory (RAM), and non-volatile programmable memory for data storage. Read only memory (ROM) may be used to accommodate security data and the
10 transponder operating system instructions which, in conjunction with the processing circuitry provides functions such as response delay timing, data flow control and power supply switching. Random access memory (RAM) may be used to facilitate temporary data storage during transponder interrogation and response. Non-volatile programmable memory may be used to store
15 transponder data so the data is retained when the transponder 130 is in a quiescent or power-saving "sleep" state or not powered at all. Data buffers may be provided to temporarily hold incoming data following demodulation and outgoing data for modulation and interface with the antenna 134.

The RFID transponder 130 may be field powered (e.g., passive). Field
20 powered transponders collect power from the RF field generated by the interrogator or base station and convert the collected power to a DC voltage which is stored in a capacitor to provide power for operating the transponder's other circuitry. Alternatively, the RFID transponder 130 may utilize a power source (i.e., a battery) interconnected to the RFID IC 132.

25 The RFID IC 132 may be coupled to an antenna 134 which provides a means by which the transponder 130 senses the interrogating field (and/or, where appropriate, a programming field). The antenna 134 also serves as the means of transmitting the transponder response to interrogation. The RFID IC 132 and antenna 134 are preferably laminated between the outer layers 114
30 & 116 of the optical disc 100. This prevents removal of the RFID transponder

130 without physical alteration (i.e., delamination, cutting, breaking, cracking, etc.) of the disc **100**. Typically, such physical alteration will be observable upon inspection or will render the disc **100** unusable (e.g., unplayable by an optical disc drive).

5 Referring now to FIGS. 1, 2, 3, and 4, the RF transponder **130** may be a preassembled RFID transponder which is embedded or laminated between the outer layers **114** & **116** as the disc **100** is assembled. The RFID IC **132** may be mounted to a substrate **136** and bonded to an antenna **134** formed on the substrate **136**. Typical substrate materials include polyester, polyimide,
10 ceramics, FR-4 circuit board material, etc. The RFID IC **132** may be coated with an encapsulant, such as a "glob-top" epoxy, or the like which protects the circuit **132** (and bonds between the antenna **134** and circuit **132**) from damage. An aperture or cavity (not shown) may be formed in the substrate **136** allowing the insertion of the RFID IC **132** therein. In this manner, the thickness of the
15 substrate **136** is not unnecessarily added to the thickness of the RFID IC **132** so that the overall cross-sectional profile of the RF transponder **100** is reduced and will not cause a bump on the surface of the optical disc **100**.

The antenna **134** may be integrally formed on the substrate **136**. Preferably, the antenna **134** consists of a thin pattern (typically 18 to 35 micron
20 thick) formed of a conductive metal such as copper. This pattern may be formed by plating or adhering or screening a thin layer of copper (or other conductive metal) onto to the substrate **136**. The layer is then be etched to form the specific geometric configuration of the antenna **134** (a dipole antenna is shown in FIGS. 1 and 3; however, any antenna configuration, i.e., dipole,
25 folded dipole, loop, coil, spiral, meander, patch, etc., may be formed). Similarly, one or more impedance adjustment elements **138** may be integrally formed on the substrate **136** to modify the impedance of the antenna **134**. The impedance adjustment elements **138** may be lumped circuit elements, distributed microwave circuit elements, or parasitic elements that are
30 electromagnetically coupled to the antenna (i.e., not electrically connected).

Often, antennas 134 which are employed by such RFID transponders 130 include a conductive ground plane (not shown). As shown in FIG. 1 and 2, the RFID transponder 130 may be located within the annular non-storage area 128 of the optical disc 100. For this embodiment, the conductive ground plane may comprise a layer of a conductive metal (e.g., copper) formed (i.e., by plating, adhering or screening, etc.) on the side of the substrate 136 opposite the pattern. Alternatively, as shown in FIGS. 3 and 4, in single sided discs 100 such as audio CD's, CD-ROM's, etc., the RFID transponder 130 may be positioned between an outer layer 114 and the non-storage ("label") surface 136 of the data storage layer (or layers) 112 (e.g., annulus 118). The substrate of the RFID transponder 130 may space the antenna's radiator element (e.g., a dipole, patch element, etc.) from the data storage layer 112 so that the annulus 118 may form the conducting ground plane of the antenna 134.

Referring now to FIGS. 5 through 28, the RFID transponder 132 may be formed within the optical disc 100 as it is assembled (e.g., without a separate substrate 136 as shown in FIGS. 1 through 4). The antenna 134 of the RFID transponder 130 may be integrally formed on a first of the outer layers (e.g., outer layer 116). Preferably, the antenna 134 consists of a thin (typically 18 to 35 micron thick) pattern formed of a conductive metal such as copper. This pattern may be formed by plating, adhering, or screening a thin layer of copper (or other conductive metal) onto to the protective layer 116. This thin copper layer may then be etched to form the specific geometric configuration of the antenna 134 (i.e., dipole, conforming dipole, meander dipole, conforming meander dipole, loop, spiral, circular slot, curvilinear slot, monopole, patch, etc.). Similarly, one or more impedance adjustment elements 138 may be integrally formed on the substrate 136 to modify the impedance of the antenna 134. The impedance adjustment elements 138 may be lumped circuit elements, distributed microwave circuit elements, or parasitic elements that are electromagnetically coupled to the antenna (i.e., not electrically connected).

An RFID IC 132 may be bonded to the antenna 134 formed on the first protective layer 114 via conventional means such as wire bonding or the like.

The RFID transponder 130 (e.g., RFID IC 132, antenna 134, impedance adjustment elements 138, etc.) may then be laminated between the first outer layer 114 and the outer protective layer 116 or an insulating layer 140 (see FIG. 22 wherein the RFID transponder 130 utilizes a separate conducting ground plane 142, or FIG. 27 wherein the RFID transponder 130 utilizes the data storage layer 112 as a conducting ground plane).

Preferably, as shown in FIGS. 7, 22, and 24, the components forming the RFID transponder 130 (i.e., RFID IC 132, antenna 134, impedance adjustment elements 138, insulating layer 140, conducting ground plane 142, etc.) are made sufficiently thin so they may be embedded between the outer layers 114 & 116 without substantially increasing the thickness of the optical disc 100. Further, the outer layers 114 & 116 may be formed so that the thickness of the RFID transponder 130 laminated or embedded there between is accommodated (i.e., within a shallow recess molded into one or both protective layers 114 & 116).

Depending on the RF properties desired, RFID transponders 130 of the present invention may employ any of an almost unlimited number of different antennas 134 having various configurations and geometries. Several of the many possible antennas 134 which may be employed by the present invention are shown in FIGS. 5 through 28 and will now be described in detail by way of example. It should be apparent that reconfiguration of any of the antennas 134 shown herein, or substitution of other types of antennas by one skilled in the art would not depart from the scope and spirit of the invention.

Referring now to FIGS. 5 through 22, the RFID transponder 130 may be formed within the annular non-storage area 128 of the optical disc 100. This configuration may be especially desirable wherein data is stored on both sides of the optical disc 100 (e.g., the optical disc 100 has a dual sided data storage layer 112 or two oppositely facing data storage layers 112). For such optical

discs 100, placement of the RFID transponder 130 over one of the data storage layers 112 could result in less than optimum use of the data storage capacity of the disc 100.

Optical discs 100 having RFID transponders 130 employing dipole antennas are illustrated in FIGS. 5, 6, 7 and 8. As shown in FIG. 5, the antenna 134 may be a linear simple dipole antenna 144 comprising first and second linear (non-curved) dipole elements 146 & 148. Alternatively, as shown in FIG. 6, the antenna 134 may be a conforming dipole antenna 150 having dipole elements 152 & 154 which are curved to conform to the inner perimeter 126 of the data storage layer 112 (e.g., annulus 118). By curving the dipole elements 152 & 154, the conforming dipole antenna 150 may be made to have a longer length than the linear dipole antenna 144 shown in FIG. 5, while still fitting within the annular non-storage area 128.

Similarly, as shown in FIG. 8, the antenna 134 may be a meander dipole antenna 156 comprising first and second linear (non-curved) meander dipole elements 158 & 160. Alternatively, as shown in FIG. 9, the antenna 134 may be a conforming meander dipole antenna 162 having meander dipole elements 164 & 166 which are curved to conform with the inner edge 126 of the data storage layer 112 (e.g., annulus 118). The curved meander dipole elements 164 & 166 allow the conforming meander dipole antenna 162 to have a longer length than the linear meander dipole antenna 156 shown in FIG. 8, while still fitting within the annular non-storage area 128.

As shown in FIGS. 5, 6 and 9, one or more impedance adjustment elements 138 may be integrally formed on the protective layer 116 to modify the impedance of the antenna 132. The impedance adjustment elements 138 may be lumped circuit elements, distributed microwave circuit elements, or parasitic elements that are electromagnetically coupled to the antenna (i.e., not electrically connected). By way of example, the RFID transponder 130 may include a tuning stub 168 having a length and width adjusted to tune the impedance of the antenna 134. The tuning stub 168 acts

as a two conductor transmission line and may be terminated either in a short-circuit or open-circuit. A short circuited stub acts as a lumped inductor while an open-circuit stub acts as a lumped capacitor. The magnitude of the reactance of the tuning stub 168 is affected by the stub's length, width, and spacing.

5 Similarly, one or more impedance loading bars 170 may be positioned adjacent to the dipole antenna 134 so they are electromagnetically coupled to the antenna 132 to modify its impedance. The loading bars 170 may be straight as shown in FIG. 5, or curved to conform to the shape of the antenna 134 and fit within the annular non-storage area 128 of the optical disc 100 as shown in
10 FIGS. 6 and 9. Use of tuning stubs and impedance loading bars to adjust the impedance of an antenna is described in detail in U.S. Patent Application Serial No. 08/790,639 to Duan, et al. filed January 29, 1997 which is herein incorporated by reference in its entirety.

Exemplary loop antennas are shown in FIGS. 10, 11, and 12.
15 Preferably, each loop antenna 172, 174 & 176 comprises a loop shaped pattern (i.e., circular, square, rectangular, semi-circle, etc.) of a conductive metal such as copper which is integrally formed on the inner surface on the protective layer 116. Alternatively, the loop antenna 172, 174 & 176 may be formed from a thin wire fashioned in the shape of a loop, bonded to the RFID
20 IC 132 and laminated between the outer layers 114 & 116 of the optical disc 100 within the annular non-storage area 128. FIG. 10 depicts a closed loop antenna 172 while FIGS. 11 and 12 illustrate open loop antennas 174 & 176.

Referring now to FIG. 13, the antenna 134 may be a spiral antenna 178.
Preferably, the spiral antenna 178 comprises a spiral pattern of a conductive
25 metal such as copper which may be integrally formed on the inner surface on the protective layer 116. Alternatively, the spiral antenna 178 may comprise a thin wire which is spiraled around the center aperture 122. The wire is bonded to the RFID IC 132 and laminated between the outer layers 114 & 116 within the annular non-storage area 128 of the optical disc 100.

30 Referring now to FIGS. 14 and 15, exemplary slot antennas 180 & 182

are illustrated. A circular slot antenna is shown in FIG. 14. The circular slot antenna 134 preferably comprises inner and outer annular antenna elements 184 & 186 embedded or laminated between the outer layers 114 & 116 within the annular non-storage area 128 of the optical disc 100. A space or "slot" 188 is formed between the inner and outer annular antenna elements 184 & 186.

The RFID IC 132 is positioned within the slot 188 and interconnected (e.g., bonded) to each element 184 & 186. Alternately, as shown in FIG. 15, the antenna 134 may be a curvilinear slot antenna 182 comprising first and second curvilinear antenna elements 190 & 192. Preferably, the first and second curvilinear antenna elements 190 & 192 are embedded or laminated between the outer layers 114 & 116 and oriented so that a slot 194 is formed between them. The RFID IC 132 may be positioned within the slot 194 and interconnected (e.g., bonded) to each element 190 & 192.

Turning now to FIGS. 16 and 17, exemplary split monopole antennas 196 & 198 are illustrated. The split monopole antennas 196 & 198 may include a generally circular antenna element 200 & 202 embedded or laminated between the outer layers 114 & 116 within the annular non-storage area 128.

Various impedance adjustment elements 138 may be utilized to tune the impedance of the split monopole antennas 196 & 198. Such impedance adjustment elements 138 may include, but are not limited to, notches 204 formed in the antenna element 200 or distributed elements 206, 208, 210 & 212 interconnected to the RFID IC 132 or antenna element 200 & 202, or electromagnetically coupled to the antenna 196 & 198. It should be appreciated that many impedance adjustment element configurations, geometries, and placements are possible. Consequently, modification of the antennas 196 & 198 shown in FIGS. 16 and 17 by one skilled in the art to utilize other impedance adjustment elements would not depart from the scope and spirit of the invention.

Referring now to FIGS. 18, 19, 20, 21, and 22, the antenna 134 may be a patch antenna. Typical patch antennas which may be utilized with the present

invention include, but are not limited to, patch antennas having conventional geometries such as the linearly polarized patch antenna **214** shown in FIG. 18 and circularly polarized patch antenna **216** shown in FIG. 19, or alternatively, application specific geometries (e.g., geometries tailored to fit within a circular or disk shaped area) such as the conforming patch antenna **218** shown in FIG. 20 and the annular patch antenna **220** shown in FIG. 21. Such patch antennas **214, 216, 218 & 220** may include a patch element **222**, one or more impedance adjustment elements **138** and a conducting ground plane **142** (FIG. 22) laminated between the outer layers **114 & 116** of the optical disc **100** within the annular non-storage area **128**. As shown in FIG. 22, the patch element **222** and impedance adjustment elements **138** are preferably separated from the conducting ground plane **142** by an insulating layer or substrate **140**.

Referring now to FIGS. 23, 24, and 25, the metal or metallized annulus **118** forming the data storage layer **112** of the optical disc **100** may be used as at least part of the antenna of the RFID transponder **130**. As shown in FIG. 23 and 24, the RFID IC **132** may be bonded directly to the annulus **118** and laminated between the outer layers **114 & 116** within the annular non-storage area **128** of the optical disc **100**. As shown in FIG. 25, one or more impedance adjustment elements **138** may be formed within the annular non-storage area **128** of the optical disc **100** to adjust the impedance of the antenna **134** (e.g., annulus **118**). The data storage layer **112** may also be used as a parasitic loading element for a dipole or meander dipole antenna (i.e., in place of impedance loading bars **170** shown in FIGS. 5 and 6).

Turning now to FIGS. 26, 27 and 28, the metal or metallized annulus **118** may form the conducting ground plane of the antenna **134** (wherein the antenna requires a ground plane). The antenna **134** may, for example, be a patch antenna **224 & 226** including a patch element **228** and one or more impedance adjustment elements **138** suspended over a conducting ground plane. Preferably, the patch element **228** and impedance adjustment elements **138** are embedded or laminated between a first outer layer **114** of the optical

disc 100 and an insulating layer 140. The annulus 118 is similarly embedded or laminated between the insulating layer 140 and a second outer layer 118 so that the patch element 228 and impedance adjustment elements 138 are physically separated from the annulus 118 by the insulation layer 140.

5 As shown in FIG. 26, the antenna 134 may be a conforming circular patch antenna 224 having a generally curved overall shape which conforms to the curvature of the annulus 118. In this manner, the area of the patch element 228 and impedance adjustment elements 138 may be increased so that utilization of the surface area of the annulus 118 as the ground plane of the
10 antenna 134 is optimized.

 Components of the RFID transponder 130 which are interconnected with the patch element 228 may optionally be positioned within the annular non-storage area 128 of the optical disc 100. For example, in FIG. 28, the RFID IC 132 is located within the annular non-storage area 128 and interconnected to
15 patch element 228 (which is formed over the annulus 118). Similarly, impedance adjustment elements (i.e., impedance matching circuits 230 & 232) may be positioned either over the annulus (e.g., impedance matching circuit 230) or within the annular non-storage area 128 (e.g., impedance matching circuit 232). However, wherein the impedance adjustment elements 138 are
20 located within the annular non-storage area 128 of the optical disc 100, a second conducting ground plane (not shown) may be required. Referring now to FIG. 29, an optical disc 100 in accordance with an alternative embodiment of the present invention is shown. The information storage and communication circuit of this optical disc 100 may comprise an integrated circuit
25 (IC) 250 embedded or laminated between the outer layers 114 & 116 of the optical disc 100. The IC 250 may be interconnected to electrical contacts 252 mounted to the surface of the disc 100 within the annular non-storage area 128. Preferably, the IC 250 comprises control and processing circuitry and
30 random access memory (RAM), and non-volatile programmable memory for

data storage. The electrical contacts 252 preferably allow the IC 230 to communicate with an external system (i.e., an optical disc player, an optical disc recorder, etc.) to provide functions such as authentication of the optical disc 100, indexing of information recorded to the optical disc 100, enablement/disablement of playback of the optical disc 100, tracking of the number of times the optical disc 100 has been played, and the like. The electrical contacts 252 may also provide electrical power to the IC 250 for its operation. Preferably, when the optical disc 100 is recorded or played, the contacts 252 mate with contacts on the drive of the player/recorder (not shown) so that information may be communicated between the IC 250 and an external system (see FIG. 30).

Further, the IC 250 may be an RFID IC and may be coupled to both the electrical contacts 252 and an antenna (such as any of the antennas shown in FIGS. 1 through 28). In this manner, information stored in the IC 250 may be read through either the contacts 252 or through the antenna (see FIGS. 1 through 28) via an RFID interrogator. The electrical contacts 252 and the antenna may be used at the same time or separately. For example, when used simultaneously, the electrical contacts 252 may be used by a driver to provide power to the IC 250 while the antenna may be used by an interrogator to read information. Alternatively, power may be transmitted through the antenna, and information through the electrical contacts 252. When used separately, an RFID interrogator may be used at the point of sale of the disc 200, or during a similar business process (i.e., inventory, delivery, etc.), to read information stored in the IC 250. For example, the electrical contacts 252 may be used by a disc drive (i.e., in an audio CD player, compact disc drive, DVD player, etc.) to read information from the IC 250. This would allow the disc drive to be made without an RFID interrogator, thereby reducing its cost and complexity.

Referring now to FIG. 30, a system 300 for playing (and/or recording) optical discs of the present invention is shown. In an exemplary embodiment, the system 300 includes a conventional player and/or recorder (e.g., a disc

drive) 302 for reading information from or writing information to the optical disc 100, an interrogator 304 for communicating with the RFID transponder 130, and a controller 306 which integrates operation of and controls data transfer via the player/recorder 302 and interrogator 304. Memory 306 may also be
5 provided for storing information (i.e., information read from the optical disc 100 or received from the RFID transponder 130, information to be written to the optical disc 100 or RFID transponder 130, data against which information received from the RFID transponder 130 may be compared, etc.).

Wherein the system 300 is used to play (e.g., read) an optical disc 100,
10 the interrogator 304 may interrogate the RFID transponder 130 by communicating a request for data contained within the transponder's memory. Preferably, the RFID transponder 130 responds to the transmitted request by communicating the requested information. This information may then be decoded and used by the controller 306 to control operation of the player 302.

15 For example, the RFID transponder 130 may transmit a code, password, etc. which commands the controller 306 to allow the player to begin playback of the disc 100 by the system 300. Preferably, unless this code is received by the interrogator 304, the optical disc 100 could not be played by the player 302.

In this manner, the system 300 would provide a means of authenticating
20 optical discs 100 to be played, thereby making them more secure against theft or counterfeiting.

Similarly, the system 300 could be used to prevent the optical disc 100 from being viewed by a particular audience. For example, the optical disc 100 may contain information (i.e., movies, music, etc.) which would be inappropriate
25 for dissemination to a particular audience (i.e., children, employees lacking a security clearance, etc.). The system 300 could prevent an optical disc 100 containing such information from being played unless a security code is entered (i.e., by an adult, employee having an appropriate clearance, etc.) which matches a security code stored within the memory of the RFID
30 transponder 130.

The memory of the RFID transponder 130 may further include index information for the data stored on the optical disc 100. When interrogated, the RFID transponder 130 would communicate this index information to the interrogator 304. The index information could then be used to locate particular data or information stored on the disc 100. Similarly, the index information could enable or disable access to sections of information stored on the optical disc 100. In this manner, a single optical disc 100 may contain data or information which may be disseminated to a wide audience as well as information which is meant for more limited groups (i.e., classified and unclassified material, proprietary and non-proprietary data, R-rated and G-rated movies, etc.). The system 300 could interrogate the RFID transponder 130 to determine which material contained on the disc could be accessed by the particular audience using the system 300.

The interrogator 304 may also be capable of writing information to the RFID transponder 130. In this manner, information such as an access code for may be written to the RFID transponder 130 for enabling/disabling future playback of the optical disc 100. Similarly, information may be written to the RFID transponder 130 during playback. For example, a record of the usage of the disc's contents may be stored to the memory of the RFID transponder 130. The interrogator 304 may increment this record each time the optical disc 100 is played. Additional playback of the optical disc 100 could then be disabled after a predetermined number of plays.

It should be appreciated that the system 300 may include one or more electrical contacts (not shown) instead of (or in addition to) the interrogator 304 shown in FIG. 30. Preferably, these electrical contacts mate with contacts 232 of the optical disc 100 shown in FIG. 29 to allow communication between the IC 230 (FIG. 29) and the controller 306.

Referring now to FIG. 31, 32, and 33, an exemplary RFID system utilizing optical discs in accordance with the present invention are shown. The RFID system 400 includes a hand-held interrogator or reader 402 (the

interrogator may be part of a hand-held data terminal, portable computer, etc.) for interrogating the RFID transponder 130 within the optical discs 100. The interrogator reads information stored in the RFID transponder's memory. The interrogator 402 may, for example, communicate a request for data contained
5 within the transponder's memory. Preferably, the RFID transponder 130 responds to the transmitted request by communicating the requested information. The information may then be decoded and used by the interrogator 402.

As shown in FIG. 31 and 33, the RFID system 400 may, for example, be
10 used in a retail, rental, or library environment. The RFID transponder 130 of each optical disc 100 may be programmed with inventory information identifying the optical disc 100 (i.e., content, serial number, inventory number, price, etc.). The interrogator 402 may interrogate each optical disc's transponder 130 to retrieve this information. In this manner, the disc 100 may
15 be inventoried without being physically handling (e.g., removed from the shelf 404 as shown in FIG. 31 or unpacked from a shipping crate 406 as shown in FIG. 33). The inventory information may similarly be utilized to locate a particular optical disc from a group of discs.

As shown in FIG. 32, the RFID system 400 may similarly be used in
20 point-of-sale applications. Inventory information stored in the memory of the RFID transponder 130 may be read by the interrogator 402 and used during sale, rental, loan, or return transactions of an optical disc 100 with a customer or patron. The information may be used to automate the transaction and/or may be provided to a central computer system to update inventory information.
25 For example, when a customer wants to return a previously purchased disc 100 (i.e., an audio CD), a store clerk may utilize the interrogator 402 to read the RFID transponder 130 in the disc 100 to retrieve information such as, for example, when the disc 100 was purchased, the price paid for the disc 100, whether the disc 100 was properly checked out (i.e., was not stolen), and the
30 store from which the disc 100 was purchased.

The interrogator 402 may also be capable of writing or programming information to the memory of the RFID transponder 130. For example, the RFID transponder 130 may be preprogrammed with a code which would disable playback of the optical disc 100 when played by a disc playing system such as the system shown in FIG. 30. The interrogator 402 may, at the time of sale, erase this code from the RFID transponder 130 so that the customer may play the optical disc 100 after purchase or rental. Alternatively, the interrogator 402 may write a code to the RFID transponder 130 which would allow playback of the optical disc 100. In this manner, theft of RFID equipped optical discs 100 would be deterred since the stolen discs could not be played.

Referring now to FIG. 34, an RFID system 500 may be capable of automatically sorting crates or packages 502 containing optical discs of the present invention. The RFID system 500 may also automatically verify the contents of each crate 502, enable/disable the RFID transponders of each optical disc contained within the crate 502, etc., by reading information from (and/or writing or programming information to) the RFID transponder of the optical discs within the crate 502.

The RFID system 500 includes a controller or base station 504 comprising an RF transceiver 506 coupled to one or more RF antennas 508. The base station 504 may interrogate RFID transponders embedded within labels 510 adhered to the crates 502 as they are carried along the system's primary conveyor mechanism 512 past the antennas 508. Memory contained by such RFID transponders may be programmed with destination and routing information for the crate 510 to which it is attached. The base station 504 may process this information so that the crate 510 may be automatically sorted and routed to the appropriate destination. This may be accomplished, in an exemplary embodiment, by temporarily closing a gate 514 across the primary conveyor mechanism 512. The gate 514 causes the crate 502 to be diverted onto a secondary conveyor mechanism 516 corresponding to the destination and routing information contained within the RFID transponder of the " label

510.

Similarly, the base station 504 may also interrogate and/or program the RFID transponders of each optical disc contained within the crate 502 (see also FIG. 33). The optical discs' RFID transponders may, for example, be programmed with information identifying the optical disc (i.e., title, author, content, serial number, inventory number, price, etc.). The base station 504 may interrogate each optical disc's transponder to retrieve this information without physically handling the disc (e.g., removing it from the shipping crate 502). The base station 504 may then use the information to verify whether each crate contains the proper number and type of optical discs.

The base station 504 may also be capable of writing or programming information to the memory of the RFID transponder of each optical disc within the crate 502. For example, the base station 504 may program the transponder with inventory information for use by customers (i.e., serial number, title, index information, etc.). Similarly, the base station 504 could program the transponder with a code, password, etc. which would enable playback of the optical disc when played by a system such as the system shown in FIG. 30. Stolen or counterfeited optical discs would lack this coded information and thus could not be played by the system.

It is believed that the present invention and many of its attendant advantages will be understood by the foregoing description, and it will be apparent that various changes may be made in the form, construction and arrangement of the components thereof without departing from the scope and spirit of the invention or without sacrificing all of its material advantages. The form herein before described being merely an explanatory embodiment thereof, it is the intention of the following claims to encompass and include such changes.

ClaimsWhat is claimed is:

1. An optical storage medium, comprising:
an optical disc including first and second protective layers and a data storage
5 layer disposed between said first and second protective layers, said
data storage layer capable of storing optically readable information; and
a circuit disposed between said first and second protective layers adjacent to
said data storage layer, said circuit including memory for storing
information and a communication device for communicating the
10 information with an external system.
2. The optical storage medium according to claim 1, wherein said
circuit comprises an radio frequency identification (RFID) circuit.
3. The optical storage medium according to claim 1, wherein said
circuit comprises an RFID transponder laminated between the first and second
15 protective layers, the RFID transponder including:
an insulating substrate;
an antenna integrally formed on the substrate; and
a radio frequency identification integrated circuit (RFID IC) chip mounted
to said substrate and interconnected with the antenna.
- 20 4. The optical storage medium according to claim 1, wherein said
circuit comprises a radio frequency identification integrated circuit (RFID IC)
interconnected with an antenna.
5. The optical storage medium according to claim 4, wherein the
RFID IC and antenna are laminated between the first and second outer layers.

6. The optical storage medium according to claim 5, wherein the antenna has a dipole structure.

7. The optical storage medium according to claim 6, further comprising a tuning stub formed in the antenna for modifying the impedance
5 of the antenna.

8. The optical storage medium according to claim 6, further comprising a loading bar electromagnetically coupled to the antenna for modifying the impedance of the antenna.

9. The optical storage medium according to claim 6, wherein the
10 antenna is interconnected to the RFID IC via an impedance matching circuit.

10. The optical storage medium according to claim 4, wherein the antenna is a meander dipole antenna.

11. The optical storage medium according to claim 10, further comprising a tuning stub formed in the antenna for modifying the impedance
15 of the antenna.

12. The optical storage medium according to claim 10, further comprising a loading bar electromagnetically coupled to the antenna for modifying the impedance of the antenna.

13. The optical storage medium according to claim 10, wherein the
20 antenna is interconnected to the RFID IC via an impedance matching circuit.

14. The optical storage medium according to claim 4, wherein the antenna is a patch antenna.

15. The optical storage medium according to claim 14, wherein the patch antenna is a linear polarized patch antenna.

16. The optical storage medium according to claim 14, wherein the patch antenna is a circularly polarized patch antenna.

17. The optical storage medium according to claim 14, wherein the patch antenna is interconnected to the RFID IC via an impedance matching
5 circuit.

18. The optical storage medium according to claim 14, wherein said data storage layer forms the ground plane of said patch antenna.

19. The optical storage medium according to claim 4, wherein the antenna is a loop antenna.

10 20. The optical storage medium according to claim 4, wherein the antenna is a spiral antenna.

21. The optical storage medium according to claim 4, wherein said optical disc includes a circular aperture centered therein, and wherein the data storage layer comprises a metal annulus coaxial with the circular aperture so
15 that the perimeter of the circular aperture and the inner circumference of the metal annulus define a annular non-storage area on said optical disc.

22. The optical storage medium according to claim 21, wherein the RFID IC chip is laminated between the first and second protective layers within the circular non-storage area.

20 23. The optical storage medium according to claim 22, wherein the antenna is an patch antenna disposed within said circular non-storage area, said patch antenna having an annular patch element and ground plane.

24. The optical storage medium according to claim 22, wherein the antenna is a circular slot antenna disposed within said circular non-storage
25 area.

25. The optical storage medium according to claim 22, wherein the antenna is a curvilinear slot antenna disposed within the circular non-storage area and having an outer edge extending along the inner edge of the data storage layer.

5 26. The optical storage medium according to claim 22, wherein the antenna is a dipole antenna disposed within the circular non-storage area and having a generally curved shape substantially conforming to the inner edge of the data storage layer.

10 27. The optical storage medium according to claim 26, further comprising an impedance loading bar electromagnetically coupled to the antenna and disposed within the circular non-storage area.

28. The optical storage medium according to claim 26, wherein the data storage layer provides impedance loading of the antenna.

15 29. The optical storage medium according to claim 22, wherein the antenna is a meander dipole antenna disposed within the circular non-storage area and having a generally curved shape substantially conforming to the inner edge of the data storage layer.

20 30. The optical storage medium according to claim 29, further comprising an impedance loading bar electromagnetically coupled to the antenna and disposed within the circular non-storage area.

31. The optical storage medium according to claim 25, wherein the data storage layer provides impedance loading of the antenna.

25 32. The optical storage medium according to claim 22, wherein the antenna is a split monopole antenna disposed within the circular non-storage area.

33. The optical storage medium according to claim 32, further comprising an impedance tuning element coupled to the antenna and disposed within the circular non-storage area.

34. The optical storage medium according to claim 22, wherein the
5 metal annulus forms part of the antenna.

35. The optical storage medium according to claim 1, wherein the communication device comprises an electrical contact.

36. The optical storage medium according to claim 1, wherein the circuit comprises a radio frequency identification circuit and the communication
10 device comprises an electrical contact and an antenna, and wherein said RFID circuit is interconnected to both the electrical contact and the antenna.

37. A system for playing an optical disc having an integral RFID transponder, comprising:
a drive for playing the optical disc;
15 a controller interconnected with said drive for controlling playback of the optical disc by said drive; and
an interrogator interconnected with said controller, said interrogator for communicating information with the RFID transponder.

38. The system in accordance with claim 37, wherein said controller
20 uses information communicated to said interrogator from the RFID transponder to control playback of the optical disc by said drive.

39. The system in accordance with claim 38, wherein the information comprises authentication information for enabling and disabling playback of the optical disc by said drive.

40. The system in accordance with claim 38, wherein the information comprises content information for the optical disc for selectively enabling and disabling playback of a portion of the optical disc by said drive.

41. The system in accordance with claim 37, wherein the information
5 includes index information for the optical disc.

42. A system for recording an optical disc having an integral RFID transponder, comprising:

a drive for recording information to the optical disc; and
a interrogator for programing the RFID transponder.

10 43. The system in accordance with claim 42, further comprising a controller interconnected with said drive and said interrogator for controlling recording of the optical disc by said drive and programming of the RFID transponder by said interrogator.

44. The system in accordance with claim 42, wherein said
15 interrogator programs the RFID transponder with authentication information for enabling and disabling playback of the optical disc.

45. The system in accordance with claim 42, wherein said interrogator programs the RFID transponder with content information representing the content of the optical disc.

20 46. The system in accordance with claim 45, wherein the content information provides selective enabling and disabling of playback of a portion of the optical disc.

47. The system in accordance with claim 45, wherein the content information includes index information for the optical disc.

48. A radio frequency identification (RFID) system, comprising:
an interrogator having transmitting and receiving apparatus for communicating
via radio frequency; and
an optical storage medium having a radio frequency identification (RFID)
5 transponder integrally formed therein, said RFID transponder configured
for communicating with the transmitting and receiving apparatus.

49. The system according to claim 48, wherein the circuit comprises
an RFID transponder laminated between the first and second protective layers,
the RFID transponder including:
10 an antenna; and
a radio frequency identification integrated circuit (RFID IC)
interconnected with the antenna.

1/20




FIG. 1




FIG. 2

2/20




FIG. 3




FIG. 4

3/20




FIG. 5




FIG. 6




FIG. 7

4/20




FIG. 8




FIG. 9

5/20




FIG. 10




FIG. 11

FIG. 12

6/20




FIG. 13




FIG. 14

7/20




FIG. 15




FIG. 16

8/20




FIG. 17

9/20




FIG. 18




FIG. 19

10/20




FIG. 20




FIG. 21




FIG. 22

11/20




FIG. 23




FIG. 24

12/20




FIG. 25

13/20




FIG. 26




FIG. 27

15/20




FIG. 29

16/20




FIG. 30

17/20




FIG. 31




FIG. 32

19/20




FIG. 33




FIG. 34

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/23630

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G11B20/00 G11B23/28 G06K19/07

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G11B G06K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 849 734 A (TEXAS INSTRUMENTS INC) 24 June 1998 (1998-06-24)	1,2, 5-17, 19-31, 35-37, 39-43, 45-47 38,44
Y	the whole document	
X	EP 0 809 245 A (TEXAS INSTRUMENTS INC) 26 November 1997 (1997-11-26)	1,2, 4-17, 19-31, 35-37, 39,46,47 3 34
Y	column 1, line 12-39; figure 1	
A	column 2, line 21-52 column 5, line 16 -column 7, line 20 --- -/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "S" document member of the same patent family

Date of the actual completion of the international search

18 January 2000

Date of mailing of the international search report

25/01/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3018

Authorized officer

Cardigos dos Reis, F

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 99/23630

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 119 353 A (ASAKURA TORU) 2 June 1992 (1992-06-02)	1, 33
Y	column 4, line 59 -column 5, line 25 ---	34, 38, 44
X	US 5 652 838 A (LOVETT DONNA M ET AL) 29 July 1997 (1997-07-29) column 7, line 24-36; figure 2 ---	1
Y	US 4 999 742 A (STAMPFLI JEAN-MARCEL) 12 March 1991 (1991-03-12)	3
A	column 3, line 8-54; claim 1; figure 6 ---	4, 20
Y	WO 97 35273 A (FINN DAVID ;RIETZLER MANFRED (DE)) 25 September 1997 (1997-09-25) the whole document ---	34
A	US 5 786 626 A (FAVREAU NORMAND GILLES ET AL) 28 July 1998 (1998-07-28) column 9, line 21-42 ---	6, 19
A	US 5 309 163 A (NGAN YIU C ET AL) 3 May 1994 (1994-05-03) the whole document ---	7-9, 11-14, 17, 23, 27, 29, 31
A	US 5 182 570 A (NYSEN PAUL A ET AL) 26 January 1993 (1993-01-26) the whole document ---	10, 28
A	WO 93 00724 A (UNITED KINGDOM GOVERNMENT ;UNIV MANITOBA (CA)) 7 January 1993 (1993-01-07) page 9, line 29 -page 10, line 27; figures 1-13 ---	15, 16, 26
A	US 5 258 762 A (CABON PHILIPPE ET AL) 2 November 1993 (1993-11-02) abstract; figure 13 -----	24, 25

INTERNATIONAL SEARCH REPORT

Information on patent family members

Inter. Application No

PCT/US 99/23630

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0849734 A	24-06-1998	JP 10228727 A	25-08-1998
EP 0809245 A	26-11-1997	JP 10075198 A	17-03-1998
		US 5905798 A	18-05-1999
US 5119353 A	02-06-1992	JP 2230584 A	12-09-1990
US 5652838 A	29-07-1997	NONE	
US 4999742 A	12-03-1991	FR 2641102 A	29-06-1990
		AT 118632 T	15-03-1995
		DE 68921179 D	23-03-1995
		DE 68921179 T	21-09-1995
		EP 0376062 A	04-07-1990
		HK 1000220 A	06-02-1998
		JP 2220896 A	04-09-1990
		JP 2818605 B	30-10-1998
WO 9735273 A	25-09-1997	DE 19610507 A	18-09-1997
		AU 4000097 A	10-10-1997
		CA 2248788 A	25-09-1997
		DE 19654902 A	23-10-1997
US 5786626 A	28-07-1998	JP 10013296 A	16-01-1998
		SG 54473 A	16-11-1998
US 5309163 A	03-05-1994	NONE	
US 5182570 A	26-01-1993	CA 2068521 A	14-05-1991
		EP 0514378 A	25-11-1992
		WO 9107785 A	30-05-1991
WO 9300724 A	07-01-1993	NONE	
US 5258762 A	02-11-1993	FR 2643726 A	31-08-1990
		AT 120277 T	15-04-1995
		AU 629921 B	15-10-1992
		AU 5287790 A	26-09-1990
		DE 69018024 D	27-04-1995
		DE 69018024 T	16-11-1995
		EP 0429568 A	05-06-1991
		ES 2099710 T	01-06-1997
		WO 9010200 A	07-09-1990
		JP 3504433 T	26-09-1991